

Preparing to Inflate

Non-threaded CO2 cartridges (see Figure 1)

1. Insert cartridge into cup with tapered end of cartridge facing up. Thread cup slowly into pump head until cartridge begins to contact puncture pin.
2. Once cartridge contacts puncture pin, twist firmly and quickly to tighten and puncture cartridge. Failure to completely tighten cartridge may allow gas to escape.



Fig. 1

Threaded CO2 cartridges (see Figure 2)

1. Unthread and set aside cup. Slowly thread cartridge into threaded socket of pump head until cartridge begins to contact puncture pin.
2. Once cartridge contacts puncture pin, twist firmly and quickly to tighten and puncture cartridge. Failure to completely tighten cartridge may allow gas to escape.



Fig. 2

Inflating with Hurricane Quick Shot

1. Remove dust cap from tire valve. For Presta valves, unscrew metal locking barrel at tip of valve.
2. Depress tip of either type valve to ensure valve doesn't stick and to blow out any dirt or contaminants that may have settled there.
3. Press dual Presta/Schrader pump head onto tire valve stem as far as it will go.
4. Once valve stem is fully inserted in pump head, lift thumb-lock lever to "locked" position as shown in Figure 3.
5. To inflate tire, press red CO2 flow control button. Gas will flow while button is depressed and will stop when button is released. Note: Quick Shot must be used in an upright position for proper inflation (see Figure 4).
6. Once desired tire pressure is reached, release thumb-lock lever and remove pump head from valve stem.
7. Discharge any remaining gas in cartridge before removing cartridge from pump head.



Fig. 3



Fig. 4

Typical Yield* of CO2 Cartridges

TIRE SIZE	12g	16g	25g
ROAD (700C OR 27")	1 tire @ 90/100 psi	1 tire @ 125/135 psi	2 tires @ 90/100 psi
MTB (26")	1 tire @ 30 psi	1 tire @ 40 psi	2 tires @ 30+ psi or 1 tire @ 60 psi
BMX (20")	1 tire @ 45 psi	2 tires @ 30 psi	2 tires @ 45 psi

*Approximate values. Actual yield depends on tire width, temperature and other factors.

WARNING

Contents under pressure. Keep out of reach of children. Never discharge towards face or body. Completely discharge cartridge before removing from pump head. Failure to do so may result in injury. Do not store cartridges in temperatures above 120°F, in direct sunlight, in an enclosed vehicle or near any heat source.



Performance Inc.
 One Performance Way
 Chapel Hill, NC 27514
 Made in USA
 PerformanceBike.com
 PERFORMANCE and the Flying P are registered marks of Performance Inc.

40-1573



**Hurricane Quick Shot
 CO2 Inflator**

Tech Support Line 1-800-727-2453

**BACK
 PRINT @ 100%
 BLUE - 2935**