

PERFORMANCE[®]

XPORT[™]

frame adapter



*Congratulations on your purchase of the XPORT Frame Adapter.
Please read these instructions carefully before use.*

PERFORMANCE[®]

XPORT[™]

frame adapter




*Congratulations on your purchase of the XPORT Frame Adapter.
Please read these instructions carefully before use.*

Installation


1. Ensure that the bicycle saddle is securely attached to the seatpost, and the seatpost is securely installed in the bicycle frame before using the XPORT Frame Adapter.
2. Press the snap-buttons at each end of the frame adapter to open the hooks. (fig. 1).
3. Place the smaller hook around the bicycle seatpost and close the hook. (fig. 2). Ensure the snap-button is fully engaged.
4. Pull on the larger hook to extend the frame adapter tube, and secure the larger hook around the bicycle stem. Close the hook and ensure the snap-button is fully engaged. (fig. 3).
5. The bicycle can now be attached to a hitch mounted or trunk mounted bicycle carrier, using the frame adapter as the mounting point. See (fig. 4).

CAUTION


When attaching frame adapter to bicycle, ensure snap-buttons are fully engaged, and bicycle is securely attached to vehicle rack. An improperly secured bicycle may fall, causing personal injury and damage to the bicycle, your vehicle or vehicles following behind you on the road.



1



2



3



4


attach to carrier

Installation


1. Ensure that the bicycle saddle is securely attached to the seatpost, and the seatpost is securely installed in the bicycle frame before using the XPORT Frame Adapter.
2. Press the snap-buttons at each end of the frame adapter to open the hooks. (fig. 1).
3. Place the smaller hook around the bicycle seatpost and close the hook. (fig. 2). Ensure the snap-button is fully engaged.
4. Pull on the larger hook to extend the frame adapter tube, and secure the larger hook around the bicycle stem. Close the hook and ensure the snap-button is fully engaged. (fig. 3).
5. The bicycle can now be attached to a hitch mounted or trunk mounted bicycle carrier, using the frame adapter as the mounting point. See (fig. 4).

CAUTION


When attaching frame adapter to bicycle, ensure snap-buttons are fully engaged, and bicycle is securely attached to vehicle rack. An improperly secured bicycle may fall, causing personal injury and damage to the bicycle, your vehicle or vehicles following behind you on the road.



1



2



3



4

attach to carrier

Performance Tech Support 1(800)727-2453
9am-6pm EST Monday-Friday



Performance, Inc.
One Performance Way
Chapel Hill, N.C. 27514
1-800-727-2453
Made in Taiwan
www.performancebike.com
PERFORMANCE and the Flying P Logo are registered marks of Performance, Inc.

40-1635 0403_1

Performance Tech Support 1(800)727-2453
9am-6pm EST Monday-Friday



Performance, Inc.
One Performance Way
Chapel Hill, N.C. 27514
1-800-727-2453
Made in Taiwan
www.performancebike.com
PERFORMANCE and the Flying P Logo are registered marks of Performance, Inc.

40-1635 0403_1